

# PRODUCT SPECIFICATION FORM

## HARRINGTON ELECTRIC WIRE ROPE PRODUCTS

### RH / RHA THREE-PHASE ELECTRIC WIRE ROPE HOISTS/TROLLEYS

Quantity \_\_\_\_\_  
 Capacity \_\_\_\_\_  
 Lift \_\_\_\_\_  
 Headroom Needed \_\_\_\_\_  
 Configuration  D (Deck/Base Mounted or Lug Suspended Hoist)  
                    S (Standard Headroom Trolley Hoist)  
                    U (Ultra-Low Headroom Trolley Hoist)  
 Hoist Speed \_\_\_\_\_ Single \_\_\_\_\_ Dual  
 Trolley Speed \_\_\_\_\_ Single -  40 FPM  64 FPM  80 FPM  
                                    Dual -  64/16 FPM  80/20 FPM  
 Voltage \_\_\_\_\_ 230-3-60 \_\_\_\_\_ 460-3-60  
 Control Voltage 110V  
 Beam Type/Size \_\_\_\_\_  
 Beam Flange Width \_\_\_\_\_  
 Beam Radius \_\_\_\_\_ (if curved monorail)

Options:

Special Voltage \_\_\_\_\_  
 Pendant and Pendant Cord  
 Specify Drop \_\_\_\_\_  
 Choose  Unwired  Installed  
 Power Supply Cord  
 Specify Length \_\_\_\_\_  
 Choose  Unwired  Installed  
 Eye Bolt Kit  
 Trolley Travel Limit Switch  
 Weatherization (for outdoor use)

Specials: \_\_\_\_\_

Please contact Harrington's Customer Service Department for further assistance:

<b>Location</b>	<b>Phone Number</b>	<b>Fax Number</b>
Manheim, PA	800-233-3010	717-665-7432
Corona, CA	800-317-7111	951-279-7500

E-mail: [customerservice@harringtonhoists.com](mailto:customerservice@harringtonhoists.com)

Form completed by:

Name \_\_\_\_\_ Company \_\_\_\_\_

Phone \_\_\_\_\_ Fax \_\_\_\_\_