PRODUCT SPECIFICATION FORM HARRINGTON SINGLE-PHASE ELECTRIC CHAIN HOISTS

	INGLE-PHASE ELECTI Quantity Capacity		<u>-</u>	
	Lift			
	Lift Speed	C (Common) (no dual speed av	L (Low) S (Starailable)	andard)
	Voltage	115-1-60		
	Control Voltage	115V	1 1 41 41 41 1160	
	Pendant Drop	(star	ndard is 4' less than lift)	
	Power Supply Cord		hook, push or geared t	
	Suspension		motorized trolley moun Lug Trolley (s	
	Suspension	1100K	Lug 11011ey (.	see below)
	Options:	Canvas Ch	nain Container	
		Steel Chair		
			nt – Parallel to Beam	
			nt – Perpendicular to Be	eam
			·	
	Trolley Type		Geared Motor	rized
	Hand Chain Drop Travel Speed		eared trolley)) S (80 FPM)	
	Traver Speed	(no dual speed av		
	Beam Type/Size	(110 addi opoca av	anabioj	
	Beam Flange Width			
	Beam Radius	(if cu	ırved monorail)	
	Specials:			
ED SING	SLE-PHASE ELECTRIC	CHAIN HOISTS/TD	OLI EVS	
	Quantity		<u>JEEL 10</u>	
	Capacity			
	Lift		DO (D. I) DA (D.	
	Lift Speed		_ DS (Dual) DA (D	ual Adjustable)
	Voltage Control Voltage	120-1-60 120V		
	Pendant Drop		S and DS speeds – star	ndard is 3' less than lift)
	Power Supply Cord	(star	ndard is 16')	
	Chain Container	Plastic container i	s standard	
	Suspension	Hook	Trolley (see below)	
	Trolley Type		Trolley Push _	Geared
	Hand Chain Drop	(if ge	eared trolley)	
	Beam Type/Size			
	Beam Flange Width Beam Radius	(if cu	irved monorail)	
	Dealli Naulus	(11 CC	irved monorall)	
	Specials:			
Please contact I	Harrington's Custome	r Service Departme	nt for further assistar	nce:
	Location	Phone Number	Fax Number	
	Manheim, PA	800-233-3010	717-665-7432	
	Corona, CA	800-317-7111	951-279-7500	
	E-mail: custom	<u>erservice@harri</u>	ingtonhoists.com	
Form completed	l by:			
Name		Company		
<u></u>				
Phone		Fax		